


LAMP PHOTOMETRIC REPORT

MODEL: 95Livial60/BL		
POWER: 10W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 773.15 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	378.7	377.3	375.7	375.7	375.4	375.1	376.2	377.5	0- 10	36.34	36.34	4.7
20	353.5	350.9	349.2	349.1	348.9	350.3	351.7	351.9	10- 20	103.1	139.4	18
30	306.0	303.9	302.6	303.9	305.4	307.7	308.9	307.7	20- 30	152.0	291.4	37.7
40	239.5	238.0	238.6	241.6	244.6	247.9	248.4	243.8	30- 40	172.6	463.9	60
50	154.6	151.5	151.3	157.1	163.6	169.1	169.9	161.8	40- 50	156.2	620.2	80.2
60	68.60	67.19	68.09	70.52	75.14	78.95	79.50	75.31	50- 60	102.3	722.5	93.4
70	18.64	16.73	17.16	18.63	21.10	21.85	22.94	20.54	60- 70	42.54	765.0	98.9
80	0.5384	0.4527	0.3624	0.4265	0.6098	0.8921	0.9203	0.7452	70- 80	7.866	772.9	100
90	0.1592	0.1629	0.1662	0.1612	0.1160	0.1140	0.1144	0.1189	80- 90	0.2632	773.2	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: MEDIUM
 Temperature: 25.3°C
 Operators:
 Test Date: 19 December 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.265m [K=1.0000]
 Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```