

Floodlight Summary:

Report based on lamp delivering 1000 lumens.

Maximum Intensity	4575.7 cd per klm.
(Luminaire orientation as tested.)	0.0 degrees vertical
	0.0 degrees horizontal

Beam Spread	At 10% of Imax	44.7V x 44.6H
	At 50% of Imax	18.0V x 18.0H
	At 90% of Imax	6.4V x 6.7H

Beam Flux	Total	891.5 lumens per klm.
	To 10% of Imax	608.4 lumens per klm.
	To 50% of Imax	264.8 lumens per klm.
	To 90% of Imax	28.4 lumens per klm.

Upward LOR	0.0 %
Downward LOR	89.2 %

Luminaire Efficiency (Light Output Ratio)	88.7 %
---	--------

C Range: 0 - 360DEG

C Interval: 10.0DEG

Test Speed: HIGH

Temperature: 25.3°C

Operators:

Test Date: 01 September 2022

γ Range: 0 - 90DEG

γ Interval: 2.5DEG

Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456


Humidity: 65.0%

Test Distance: 6.265m [K=1.0000]

Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

NAME: 96GRF1/51524	TYPE: 96GRF1/51524	WEIGHT: 1
SPEC.:	DIM.: F 120 x 90	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: 5 Circle	Shielding Angle:



DATA OF LAMP		PHOTOMETRIC DATA	
MODEL	96GRF1/51524	Imax (cd)	1830
NOMINAL POWER (W)	5	AVAILABILITY (%)	60.1
RATED VOLTAGE (V)	230	Avai. FLUX (lm)	240.4
NOMINAL FLUX (lm)	400	LOR (%)	88.7
LAMPS INSIDE	1	TOTAL FLUX (lm)	354.9
TEST VOLTAGE (V)	230	θ @50% (H,V)	18,18DEG

VERTICAL (DEG)	AREA FLUX DIAGRAM																UNIT:lm		Φ t	Φ a
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.00
90	0.00	0.00	0.00	0.00	0.01	0.02	0.03	0.03	0.04	0.04	0.03	0.03	0.02	0.01	0.00	0.00	0.00	0.00	0.26	0.00
80	0.00	0.00	0.00	0.02	0.03	0.05	0.08	0.10	0.12	0.12	0.11	0.08	0.06	0.04	0.02	0.01	0.00	0.00	0.84	0.00
70	0.00	0.00	0.01	0.04	0.07	0.12	0.19	0.26	0.30	0.30	0.26	0.20	0.13	0.08	0.04	0.01	0.00	0.00	2.03	0.00
60	0.00	0.00	0.02	0.06	0.13	0.26	0.45	0.60	0.68	0.67	0.59	0.46	0.29	0.15	0.07	0.03	0.00	0.00	4.47	0.00
50	0.00	0.01	0.03	0.09	0.22	0.46	0.80	1.22	1.59	1.61	1.29	0.86	0.52	0.25	0.10	0.04	0.01	0.00	9.08	0.00
40	0.00	0.01	0.04	0.13	0.32	0.68	1.49	2.82	4.13	4.22	3.02	1.66	0.79	0.37	0.14	0.05	0.01	0.00	19.9	1.81
30	0.00	0.01	0.05	0.16	0.41	1.00	2.62	5.82	10.3	10.6	6.24	2.92	1.14	0.46	0.17	0.05	0.01	0.00	42.0	29.7
20	0.00	0.01	0.05	0.18	0.48	1.28	3.64	9.89	32.4	34.2	10.6	4.00	1.42	0.52	0.19	0.06	0.01	0.00	98.9	88.8
10	0.00	0.01	0.05	0.18	0.50	1.29	3.65	9.88	32.1	34.0	10.6	3.96	1.43	0.53	0.20	0.06	0.01	0.00	98.4	88.3
0	0.00	0.01	0.05	0.16	0.45	1.05	2.64	5.87	10.5	10.7	6.17	2.82	1.14	0.46	0.18	0.05	0.01	0.00	42.2	29.8
-10	0.00	0.01	0.04	0.13	0.35	0.73	1.50	2.83	4.15	4.22	2.96	1.62	0.77	0.37	0.14	0.04	0.01	0.00	19.9	1.94
-20	0.00	0.01	0.03	0.10	0.23	0.46	0.78	1.22	1.60	1.61	1.26	0.82	0.48	0.25	0.10	0.03	0.01	0.00	9.00	0.00
-30	0.00	0.00	0.02	0.07	0.14	0.26	0.42	0.58	0.71	0.71	0.59	0.43	0.27	0.15	0.07	0.02	0.00	0.00	4.45	0.00
-40	0.00	0.00	0.02	0.04	0.09	0.14	0.20	0.27	0.31	0.32	0.27	0.21	0.14	0.08	0.04	0.02	0.00	0.00	2.16	0.00
-50	0.00	0.00	0.01	0.02	0.04	0.07	0.09	0.11	0.12	0.12	0.12	0.10	0.07	0.04	0.02	0.01	0.00	0.00	0.94	0.00
-60	0.00	0.00	0.00	0.00	0.01	0.02	0.03	0.03	0.04	0.04	0.04	0.03	0.02	0.01	0.01	0.00	0.00	0.00	0.28	0.00
-70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.00
-80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	-90	-80	-70	-60	-50	-40	-30	-20	HORIZONTAL (DEG)	20	30	40	50	60	70	80	90			
Φ t	0.00	0.08	0.43	1.38	3.50	7.89	18.6	41.6	99.1	103	44.1	20.2	8.70	3.76	1.48	0.47	0.09	0.00	355	---
Φ a	0.00	0.00	0.00	0.00	0.00	0.00	1.21	27.6	87.0	91.6	30.6	2.33	0.00	0.00	0.00	0.00	0.00	0.00	---	240

one-half-peak spread: U:8.9,D:9.2 , L:8.6,R:9.6

NEMA Beam Type: Type 3

C Range: 0 - 360DEG

C Interval: 10.0DEG

Test Speed: HIGH

Temperature:25.3°C

Operators:

Test Date:01 September 2022

γ Range: 0 - 90DEG

γ Interval: 2.5DEG

Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456


Humidity:65.0%

Test Distance:6.265m [K=1.0000]

Remarks:

ISOCANDELA DIAGRAM

NAME: 96GRF1/51524	TYPE: 96GRF1/51524	WEIGHT: 1
SPEC.:	DIM.: F 120 x 90	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: 5 Circle	Shielding Angle:




C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature:25.3°C
 Operators:
 Test Date:01 September 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity:65.0%
 Test Distance:6.265m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM


NAME: 96GRF1/51524	TYPE: 96GRF1/51524	WEIGHT: 1
SPEC.:	DIM.: F 120 x 90	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: 5 Circle	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3°C
Operators:
Test Date: 01 September 2022

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity: 65.0%
Test Distance: 6.265m [K=1.0000]
Remarks:

Planar Illuminance Curve




C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature: 25.3°C
 Operators:
 Test Date: 01 September 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.265m [K=1.0000]
 Remarks:

AAI Figure

NAME: 96GRF1/51524	TYPE: 96GRF1/51524	WEIGHT: 1
SPEC.:	DIM.: F 120 x 90	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: 5 Circle	Shielding Angle:



Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG

C Interval: 10.0DEG

Test Speed: HIGH

Temperature:25.3°C

Operators:

Test Date:01 September 2022

γ Range: 0 - 90DEG

γ Interval: 2.5DEG

Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456

Humidity:65.0%

Test Distance:6.265m [K=1.0000]

Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: 96GRF1/51524	TYPE: 96GRF1/51524	WEIGHT: 1
SPEC.:	DIM.: F 120 x 90	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: 5 Circle	Shielding Angle:

Table--1

UNIT: cd

H (DEG) V (DEG)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-85	0.00	0.00	0.00	0.01	0.02	0.01	0.00	0.02	0.04	0.03	0.03	0.04	0.06	0.04	0.03	0.03	0.04	0.03	0.01
-80	0.00	0.00	0.00	0.01	0.04	0.04	0.04	0.07	0.11	0.12	0.14	0.20	0.25	0.28	0.30	0.36	0.42	0.43	0.43
-75	0.00	0.00	0.00	0.03	0.06	0.08	0.11	0.23	0.34	0.46	0.55	0.67	0.83	0.97	1.09	1.15	1.20	1.22	1.23
-70	0.00	0.00	0.01	0.05	0.10	0.21	0.35	0.61	0.83	1.10	1.40	1.67	1.85	2.01	2.10	2.16	2.15	2.18	2.19
-65	0.00	0.00	0.02	0.08	0.22	0.46	0.79	1.14	1.52	1.95	2.43	2.82	3.15	3.41	3.56	3.64	3.66	3.74	3.77
-60	0.00	0.00	0.04	0.10	0.41	0.78	1.23	1.71	2.28	2.92	3.53	4.08	4.55	4.97	5.43	5.78	5.95	6.13	6.22
-55	0.00	0.01	0.05	0.24	0.63	1.14	1.68	2.34	3.12	3.94	4.73	5.52	6.28	7.22	8.01	8.90	9.60	10.1	10.3
-50	0.00	0.01	0.07	0.38	0.85	1.47	2.14	3.02	4.01	5.07	6.22	7.55	9.03	10.5	12.1	13.6	15.0	16.1	16.9
-45	0.00	0.02	0.09	0.51	1.09	1.77	2.61	3.72	5.07	6.53	8.17	10.3	12.5	14.9	17.4	19.4	21.6	23.0	23.6
-40	0.00	0.02	0.11	0.64	1.30	2.07	3.07	4.51	6.28	8.30	10.8	13.7	17.3	20.6	23.9	27.6	30.8	32.8	33.6
-35	0.00	0.03	0.17	0.75	1.47	2.35	3.62	5.38	7.57	10.5	14.0	18.3	22.4	27.6	33.4	39.6	46.6	51.0	52.8
-30	0.00	0.03	0.22	0.86	1.62	2.67	4.20	6.23	9.12	12.9	18.0	22.9	29.4	37.9	49.3	61.2	74.4	84.3	86.0
-25	0.00	0.03	0.26	0.96	1.77	2.95	4.78	7.13	10.8	15.8	22.0	28.6	38.0	52.6	70.7	94.2	116	133	141
-20	0.00	0.04	0.29	1.03	1.92	3.26	5.27	7.93	12.5	18.9	25.4	34.3	49.6	71.9	102	140	181	213	227
-15	0.00	0.04	0.31	1.08	2.03	3.52	5.65	8.87	14.2	21.1	28.2	39.6	61.2	93.4	138	198	260	322	351
-10	0.00	0.04	0.32	1.12	2.13	3.70	5.93	9.56	15.3	22.5	30.6	46.0	72.6	113	176	255	385	622	734
-5	0.00	0.04	0.32	1.13	2.18	3.81	6.10	9.96	15.6	22.9	32.2	49.8	80.0	128	202	312	605	1127	1473
0	0.00	0.04	0.31	1.12	2.21	3.85	6.14	10.1	15.4	22.8	32.8	50.7	82.8	134	213	341	706	1440	1830
5	0.00	0.04	0.31	1.11	2.22	3.83	6.04	9.90	15.0	21.6	31.5	48.7	80.9	127	202	314	612	1143	1476
10	0.00	0.04	0.30	1.08	2.18	3.74	5.82	9.43	14.4	19.9	28.9	44.7	71.5	113	175	253	382	616	807
15	0.00	0.04	0.28	1.03	2.10	3.59	5.49	8.65	13.4	18.5	25.5	38.4	60.2	93.4	137	197	257	315	342
20	0.00	0.04	0.26	0.96	1.97	3.38	5.08	7.67	12.2	16.7	22.6	31.8	48.3	71.9	101	137	178	210	222
25	0.00	0.04	0.23	0.87	1.80	3.10	4.63	6.81	10.6	14.7	19.7	26.3	36.6	52.1	72.3	94.0	115	134	140
30	0.00	0.04	0.20	0.77	1.59	2.80	4.16	5.81	8.81	12.6	16.8	22.0	29.1	37.1	48.1	61.8	74.5	83.1	88.1
35	0.00	0.04	0.17	0.65	1.38	2.46	3.66	5.03	7.09	10.1	13.8	17.9	23.1	28.4	33.8	39.2	45.7	50.7	52.5
40	0.00	0.03	0.13	0.53	1.13	2.08	3.14	4.26	5.69	7.74	10.7	14.1	18.0	22.0	25.4	28.0	30.4	31.8	32.0
45	0.00	0.03	0.11	0.39	0.90	1.68	2.59	3.53	4.54	5.94	7.64	10.3	13.0	16.5	18.8	20.1	21.2	21.8	22.0
50	0.00	0.02	0.09	0.27	0.64	1.29	2.02	2.80	3.60	4.59	5.68	6.92	8.79	10.9	12.7	13.9	14.7	15.2	15.1
55	0.00	0.02	0.08	0.19	0.45	0.88	1.47	2.07	2.72	3.35	4.09	4.85	5.73	6.71	7.61	8.77	9.46	9.73	9.64
60	0.00	0.02	0.06	0.11	0.27	0.52	0.96	1.42	1.88	2.35	2.77	3.28	3.86	4.41	4.91	5.37	5.72	5.88	5.91
65	0.00	0.01	0.05	0.09	0.16	0.31	0.56	0.88	1.20	1.50	1.81	2.07	2.40	2.72	3.12	3.45	3.72	3.86	3.92
70	0.00	0.01	0.04	0.06	0.08	0.16	0.28	0.47	0.71	0.92	1.13	1.32	1.48	1.67	1.87	2.07	2.25	2.36	2.44
75	0.00	0.01	0.03	0.04	0.04	0.08	0.11	0.18	0.24	0.40	0.56	0.68	0.78	0.88	0.97	1.03	1.08	1.13	1.17
80	0.00	0.01	0.02	0.02	0.02	0.04	0.06	0.07	0.07	0.09	0.12	0.17	0.22	0.26	0.27	0.29	0.30	0.33	0.36
85	0.00	0.01	0.01	0.01	0.00	0.02	0.03	0.03	0.03	0.04	0.05	0.04	0.03	0.04	0.05	0.04	0.02	0.04	0.05
90	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01

C Range: 0 - 360DEG

C Interval: 10.0DEG

Test Speed: HIGH

Temperature:25.3°C

Operators:

Test Date:01 September 2022

γ Range: 0 - 90DEG

γ Interval: 2.5DEG

Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456

Humidity:65.0%

Test Distance:6.265m [K=1.0000]

Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: 96GRF1/51524	TYPE: 96GRF1/51524	WEIGHT: 1
SPEC.:	DIM.: F 120 x 90	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: 5 Circle	Shielding Angle:

Table--2

UNIT: cd

H (DEG) V (DEG)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-85	0.04	0.07	0.06	0.04	0.05	0.06	0.04	0.03	0.04	0.04	0.03	0.01	0.02	0.02	0.01	0.00	0.00	0.00	
-80	0.40	0.37	0.35	0.33	0.32	0.31	0.26	0.20	0.17	0.14	0.09	0.05	0.05	0.05	0.02	0.00	0.01	0.00	
-75	1.21	1.19	1.15	1.09	1.01	0.87	0.76	0.66	0.52	0.39	0.28	0.12	0.10	0.08	0.04	0.01	0.01	0.00	
-70	2.27	2.31	2.34	2.30	2.19	2.01	1.74	1.45	1.19	0.96	0.70	0.47	0.26	0.12	0.06	0.02	0.01	0.00	
-65	3.87	3.91	3.90	3.78	3.55	3.26	2.88	2.43	1.94	1.54	1.19	0.85	0.55	0.26	0.09	0.03	0.02	0.00	
-60	6.27	6.16	5.92	5.57	5.13	4.65	4.13	3.50	2.82	2.21	1.69	1.26	0.85	0.48	0.12	0.05	0.02	0.00	
-55	10.3	9.86	9.15	8.30	7.42	6.49	5.62	4.77	3.85	3.03	2.24	1.67	1.17	0.69	0.26	0.07	0.03	0.00	
-50	16.0	14.9	13.8	12.3	10.8	9.32	7.83	6.46	5.22	4.02	2.95	2.10	1.49	0.91	0.40	0.09	0.03	0.00	
-45	23.1	21.6	19.5	17.5	15.3	13.0	10.7	8.56	6.72	5.16	3.76	2.58	1.79	1.13	0.54	0.10	0.04	0.00	
-40	32.9	31.1	28.1	24.5	20.9	17.6	14.5	11.5	8.66	6.43	4.62	3.10	2.13	1.34	0.68	0.13	0.04	0.00	
-35	51.4	47.6	41.3	34.9	29.2	23.4	18.8	15.0	11.2	7.86	5.54	3.75	2.47	1.56	0.80	0.20	0.05	0.00	
-30	85.1	75.3	63.4	52.4	40.7	31.7	24.0	19.0	14.0	9.72	6.54	4.41	2.85	1.76	0.92	0.26	0.05	0.00	
-25	135	120	98.7	76.0	57.8	41.2	30.1	22.5	17.0	11.9	7.55	5.03	3.18	1.97	1.02	0.30	0.06	0.00	
-20	216	187	147	108	77.0	54.4	36.8	25.8	19.2	13.7	8.53	5.61	3.56	2.16	1.11	0.34	0.06	0.00	
-15	330	269	208	147	99.5	66.8	43.3	29.1	21.2	15.1	9.73	6.09	3.85	2.32	1.18	0.37	0.06	0.00	
-10	654	406	270	189	121	78.6	50.9	32.8	22.8	16.0	10.4	6.40	4.05	2.46	1.22	0.38	0.07	0.00	
-5	1223	660	331	218	140	87.8	55.8	34.7	23.6	16.5	10.8	6.55	4.18	2.55	1.25	0.39	0.07	0.00	
0	1524	846	355	229	147	90.6	57.7	35.0	23.7	16.5	10.8	6.56	4.22	2.60	1.26	0.39	0.07	0.00	
5	1234	671	329	218	141	87.1	55.1	34.0	23.3	16.2	10.5	6.49	4.18	2.59	1.26	0.38	0.07	0.00	
10	649	406	270	192	126	80.1	50.6	31.8	22.2	15.5	10.0	6.27	4.08	2.52	1.23	0.37	0.07	0.00	
15	322	268	212	151	103	68.5	43.9	28.9	20.8	14.5	9.29	5.91	3.92	2.42	1.17	0.35	0.07	0.00	
20	214	189	149	112	80.2	55.0	36.6	26.0	19.0	13.3	8.45	5.43	3.69	2.28	1.08	0.32	0.07	0.00	
25	137	120	100	78.5	58.7	41.7	30.7	22.7	16.8	11.5	7.54	4.96	3.40	2.09	0.97	0.29	0.06	0.00	
30	83.1	77.4	65.9	53.2	41.3	32.6	25.3	19.3	14.5	9.68	6.48	4.49	3.08	1.88	0.82	0.25	0.06	0.00	
35	51.5	47.7	41.6	35.9	30.3	25.4	20.8	16.2	11.4	7.92	5.53	3.97	2.70	1.63	0.67	0.20	0.06	0.00	
40	31.9	30.7	28.6	26.4	23.1	20.1	16.5	12.5	8.72	6.39	4.64	3.40	2.32	1.35	0.55	0.15	0.05	0.00	
45	21.9	21.0	19.7	18.4	16.8	14.7	11.5	8.77	6.58	5.09	3.76	2.79	1.91	1.06	0.44	0.13	0.05	0.00	
50	14.9	14.3	13.5	12.3	11.0	9.17	7.51	6.18	4.95	3.82	2.96	2.20	1.49	0.76	0.33	0.11	0.04	0.00	
55	9.56	9.19	8.51	7.68	6.96	6.12	5.22	4.37	3.52	2.80	2.22	1.64	1.08	0.55	0.23	0.09	0.04	0.00	
60	5.94	5.81	5.49	5.10	4.63	4.09	3.45	2.85	2.36	1.97	1.56	1.14	0.70	0.34	0.14	0.07	0.03	0.00	
65	3.89	3.79	3.57	3.29	2.92	2.54	2.15	1.86	1.59	1.33	1.04	0.73	0.39	0.21	0.10	0.06	0.03	0.00	
70	2.41	2.33	2.17	1.97	1.73	1.53	1.37	1.21	1.02	0.81	0.59	0.33	0.20	0.11	0.06	0.05	0.02	0.00	
75	1.15	1.11	1.05	0.99	0.91	0.82	0.72	0.63	0.49	0.34	0.22	0.12	0.09	0.05	0.04	0.03	0.02	0.00	
80	0.35	0.33	0.32	0.30	0.27	0.22	0.19	0.14	0.09	0.07	0.07	0.06	0.04	0.02	0.02	0.02	0.01	0.00	
85	0.05	0.04	0.06	0.07	0.05	0.03	0.04	0.05	0.04	0.02	0.03	0.04	0.02	0.00	0.01	0.01	0.01	0.00	
90	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	

C Range: 0 - 360DEG

C Interval: 10.0DEG

Test Speed: HIGH

Temperature:25.3°C

Operators:

Test Date:01 September 2022

γ Range: 0 - 90DEG

γ Interval: 2.5DEG

Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456

Humidity:65.0%

Test Distance:6.265m [K=1.0000]

Remarks: